

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
2 June 2005 (02.06.2005)


PCT

(10) International Publication Number  
WO 2005/049107 A2

- (51) International Patent Classification<sup>1</sup>: A61M
- (21) International Application Number: PCT/IL.2004/001065
- (22) International Filing Date: 18 November 2004 (18.11.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/520,667 18 November 2003 (18.11.2003) US  
60/581,711 23 June 2004 (23.06.2004) US
- (71) Applicant (for all designated States except US): NANA-PASS TECHNOLOGIES LTD. (IL/IL); 18 Haneviim St., 31043 Haifa (IL.)
- (72) Inventors; and  
(75) Inventors/Applicants (for US only): YESHURUN, Yehushua (IL/IL); 17 Avshalom St., 34403 Haifa (IL). HEFETZ, Meir (IL/IL); 24954 Mizpeh Harashim (IL)
- (74) Agent: FRIEDMAN, Mark; 7 Jabotinsky St., 52520 Ramat Gan (IL.).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: ENHANCED PENETRATION SYSTEM AND METHOD FOR SLIDING MICRONEEDLES



(57) Abstract: A microneedle device for transporting fluid through a surface of a biological barrier, the device including a fluid transport configuration, an abutment member and a displacement device. The fluid transport configuration includes a substrate having a substantially planar surface having a plurality of microneedles projecting therefrom. The abutment member has an abutment surface for abutting the biological barrier. The displacement device is configured for generating a relative lateral sliding movement between the surface of the biological barrier and the fluid transport configuration in a sliding direction of the microneedles. The microneedles are arranged so that a leading microneedle defines an effective area which is void of another microneedle. The

effective area is defined as an area marked out by translating the base area of the leading microneedle, by the height of the leading microneedle, in a direction opposite to the sliding direction.



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *without international search report and to be republished upon receipt of that report*